

**For measuring**

- Track gauge
- Superelevation

- Light-weight, handy size
  - Aluminium rectangular tube
  - Gold anodised, insulated
  - Superelevation measuring integrated
  - Weight ~2.5 kg
- Other gauges available upon request.

**Measuring range:**

- Track gauge 1415 mm to 1500 mm
- Superelevation -30 mm to +200 mm
- Measuring accuracy +/-0.5 mm
- Scale graduation 1 graduation mark = 1 mm



## ACCESSORIES

- 9808337007 Measuring bolt set for grooved rails
- 9808307014 Transport box for gauge 1435
- 9002200216 Transport bag
- R\_\_KAL\_INT Calibration

**For measuring**

- Track gauge
- Check rail gauge
- Flange groove
- Back to back distance
- Cross level on flat bottom and grooved rails

- Combined track construction measuring device for new track and maintenance
  - All values are clearly shown on a display and therefore can be viewed easily at one glance
  - Made of gold anodised sturdy aluminium tube, with integrated electronics and measuring mechanics
  - With turning knob for gauge adjustment
  - Weight ~2.5 kg
- Other gauges available upon request.

**Measuring range:**

- Track gauge -20 mm/+40 mm
- Superelevation +/- 200 mm
- Flange groove 20 - 128 mm
- Check rail gauge 1347 - 1455 mm
- Back to back distance 1327 - 1435 mm



## ACCESSORIES

- 9808350008 Transport case
- R\_\_KAL\_INT Calibration
- 9002200216 Transport bag



Transport case